

Spirent TestCenter™


VXLAN Emulation

VXLANs are an overlay network used to create large private networks of virtual machines across existing layer 2 and 3 networks. Spirent TestCenter VXLAN emulation provides a unique and easy to use interface that creates large multi-segment, multi-virtual machine, and multiple VTEPs to allow for validation of your VXLAN-enabled devices

Features

- Report VTEP forwarding rate at various table capacities utilizing the Spirent benchmarking packages: RFC 2544, RFC 2889 and RFC 3918
- Test network delays and buffer capacity with nanoseconds accurate data plane latency
- Verify flooding and leakage across various VXLAN segments
- Verify thousands of VTEPs, millions of VMs with in a single segment, and VMs across multiple segments and its effect on the forwarding rate of the DUT

Spirent's VXLAN emulation package allows for complete testing coverage from simple functional to complex, large-scaled data center configurations. Spirent's VXLAN emulation package supports multiple address learning methods (unicast, IGMP, PIM, EVPN) that can scale to tens of thousands of emulated virtual machines (VMs) behind thousands of emulated VTEPs.





Benefits

- Create high-scale, complex topologies to validate both physical and virtual VXLAN-enabled DUTs
- Validate the control plane scalability of VXLAN devices by emulating various host protocols
- Generate VXLAN encapsulated traffic to validate physical VXLAN device forwarding performance

Applications

- VTEP segment capacity: Determine how many VNIs and Segments a single device can handle and learn
- VTEP performance: Run forwarding rate test at various capacities while monitoring traffic impurities as virtual segments increase
- Traffic convergence time: Determine the duration your device(s) take to update the VTEPs with new address destination tables for traffic to be forwarded correctly
- L2-7 traffic verification: Each emulated VM supports a fully functioning protocol stack which will allow for testing L2/3 traffic in addition to L4-7 for firewall or other application aware devices in the VXLAN overlay network
- Traffic Leakage or Flooding: Verify traffic is not inadvertently being forwarded on incorrect VXLAN segments which would produce a security and privacy risk for your customers

Using Spirent’s Topology Emulation, the VXLAN VTEP and VMs that are emulated have the capability of running any of Spirent TestCenter protocols (including application layer: HTTP, FTP, Video) over a fully encapsulated VXLAN segment. This will quickly find the capacity and forwarding rate of any VTEP, VTEP Gateway, switch, firewall or forwarding device supporting VXLANs.



About Spirent Communications

Spirent Communications (LSE: SPT) is a global leader with deep expertise and decades of experience in testing, assurance, analytics and security, serving developers, service providers, and enterprise networks.

We help bring clarity to increasingly complex technological and business challenges.

Spirent’s customers have made a promise to their customers to deliver superior performance. Spirent assures that those promises are fulfilled.

For more information, visit: www.spirent.com

AMERICAS 1-800-SPIRENT
+1-800-774-7368
sales@spirent.com

US Government & Defense
info@spirentfederal.com
spirentfederal.com

EUROPE AND THE MIDDLE EAST
+44 (0) 1293 767979
emeainfo@spirent.com

ASIA AND THE PACIFIC
+86-10-8518-2539
salesasia@spirent.com

Technical Specifications

- Emulates 32K to 64K VMs per port
- Emulates 4000 VTEPs per port
- Each VM can have unique or same segment id (24-bit, 16 million + ids)
- Supports Layer 2 and Layer 3 encapsulation
- End-to-End L2-7 Testing
- VXLAN encapsulations: HTTP, FTP, DHCP, IGMP, BGP, etc.
- Unicast /multicast learning modes supported on a single VTEP
- EVPN (RFC 7432) Control Plane Learning Mode
- IGMP and PIM supported for multicast Learning
- VM Mobility between VTEPs
- Wizard to create simple to complex VXLAN configurations with traffic
- Spirent’s unique traffic statistics to verify inner and outer addresses, VNIs, latency, packet loss
- Dynamic Result Views to quickly isolate problem areas
- Auto Select on UDP Source Port for Hashing
- Destination Port modifiable (4789)
- Dynamically start / stop VTEPs
- Flooded or VXLAN Leakage Results
- Easy-to-read Wireshark capture decodes

Supported platforms	<ul style="list-style-type: none"> ▪ Supported on the Spirent MX, MX2, FX, FX2, DX and DX2 family modules ▪ Supported on HyperMetrics CV modules ▪ Supported on HyperMetrics neXt modules ▪ Supported on Spirent TestCenter Virtual ▪ Supported on Spirent TestCenter C1 and C50 																
Requirements	<ul style="list-style-type: none"> ▪ Standard Spirent TestCenter with Traffic Generator and Analyzer 																
Ordering information	<table border="0"> <tr> <td>▪ VXLAN Emulation</td> <td>BPK-1310A</td> </tr> </table>	▪ VXLAN Emulation	BPK-1310A														
▪ VXLAN Emulation	BPK-1310A																
Related	<table border="0"> <tr> <td>▪ EVPN Emulation</td> <td>BPK-1311A</td> </tr> <tr> <td>▪ FCoE/DCBX Emulation</td> <td>BPK-1081A</td> </tr> <tr> <td>▪ LISP Emulation</td> <td>BPK-1181A</td> </tr> <tr> <td>▪ OpenFlow Compliance Test Suite</td> <td>VCS-KIT-01-1Y</td> </tr> <tr> <td>▪ OpenFlow Controller Emulation</td> <td>BPK-1193A</td> </tr> <tr> <td>▪ OpenFlow Switch Emulation</td> <td>BPK-1195A</td> </tr> <tr> <td>▪ SPB Emulation</td> <td>BPK-1182A</td> </tr> <tr> <td>▪ TRILL Emulation</td> <td>BPK-1187A</td> </tr> </table>	▪ EVPN Emulation	BPK-1311A	▪ FCoE/DCBX Emulation	BPK-1081A	▪ LISP Emulation	BPK-1181A	▪ OpenFlow Compliance Test Suite	VCS-KIT-01-1Y	▪ OpenFlow Controller Emulation	BPK-1193A	▪ OpenFlow Switch Emulation	BPK-1195A	▪ SPB Emulation	BPK-1182A	▪ TRILL Emulation	BPK-1187A
▪ EVPN Emulation	BPK-1311A																
▪ FCoE/DCBX Emulation	BPK-1081A																
▪ LISP Emulation	BPK-1181A																
▪ OpenFlow Compliance Test Suite	VCS-KIT-01-1Y																
▪ OpenFlow Controller Emulation	BPK-1193A																
▪ OpenFlow Switch Emulation	BPK-1195A																
▪ SPB Emulation	BPK-1182A																
▪ TRILL Emulation	BPK-1187A																